

## Application of CO<sub>2</sub>-Saturated Water Flooding as a Prospective Improved Oil Recovery and CO<sub>2</sub> Storage Strategy: Experimental and Simulation Study

*Nader Mosavat and Farshid Torabi*

*Petroleum Systems Engineering, Faculty of Engineering and Applied Science, University of Regina, Regina, Canada*

### Abstract

In this study, prior to flooding tests a number of CO<sub>2</sub> solubility measurement tests for CO<sub>2</sub>-oil and CO<sub>2</sub>-brine systems were conducted in order to determine the effect of operating conditions on the capacity of reservoir fluids to dissolve the injected CO<sub>2</sub>. Next, series of flooding experiments were carried out using unconsolidated sand-pack, synthetic brine, and real Bakken light crude oil to investigate the performance of CO<sub>2</sub>-saturated water injection as a potential strategy for improving light oil recovery and at the same time permanent CO<sub>2</sub> storage. Both solubility and flooding tests were performed at various operating pressures in the range of  $P = 0.7$  MPa to 10.3 MPa and two constant operating temperatures of  $T = 25$  °C and 40 °C.

According to the results of CO<sub>2</sub> solubility measurement tests at constant temperatures, an increase in CO<sub>2</sub> solubility values was observed for both CO<sub>2</sub>-brine and CO<sub>2</sub>-oil systems when the equilibrium pressure increases. Furthermore, it was revealed that for both aforementioned systems, the solubility of CO<sub>2</sub> reduces when temperature increased. In terms of oil recovery, it was found that the ultimate oil recovery factor of CO<sub>2</sub>-saturated water flooding is consistently more than that of conventional water flooding leading this technique to be a more viable option as a means of improved oil recovery technique. In this study, flooding tests conducted at pressure of  $P = 10.3$  MPa and temperature of  $T = 25$  °C, verified that injection of CO<sub>2</sub>-saturated water resulted in improving the conventional water flooding oil recovery factor by about 19.0% and 12.5% of OOIP for secondary and tertiary scenarios, respectively. From CO<sub>2</sub> storage point of view, it was revealed that mixing CO<sub>2</sub> with injected water noticeably provides permanent, safe, and practical CO<sub>2</sub> storage together with considerable oil recovery improvement in light oil systems.

It was also found that introducing CO<sub>2</sub> to the oil reservoirs through injection water provides great opportunity to lock large quantity of CO<sub>2</sub> inside the porous medium with high retention factor. Results of this study showed that both secondary and tertiary scenarios of CO<sub>2</sub>-saturated water flooding are favourable with the storage capacity between 34% to 45% of the injected CO<sub>2</sub> in the sand-pack model.